

- (2) CURB: 11GA (.090)ALUMINUM CURB COUNTERFLASH WITH EZ TABS.
- 3 FINISH: MILL
- 4 INSULATION: 1" POLYISO R-6 (5.6 LTTR)IN CURB,
  - 1" POLYSTYRENE R-4 (3.8 LTTR)IN COVER.
- (5) GASKET: EXTRUDED EPDM RUBBER ADHESIVE BACKED GASKET SEAL COUNTINUOUS AROUND COVER.
- 6 SPRING: GAS SPRING WITH DAMPER FOR SMOOTH, CONTROLLED, COUNTERBALANCED LIFT ASSISTANCE.
- (7) **HINGE**: PINTLE HINGE WITH STAINLESS STEEL HINGE PINS.
- (8) HOLD OPEN ARM: ZINC PLATED STEEL AUTOMATIC HOLD OPEN ARM LOCKS COVER IN FULLY OPEN POSITION WITH RED POLYPROPYLENE GRIP HANDLE PULL RELEAROUGH OPENING 30" (WIDTH) x 54" (LENGTH)

- AGAINST 20PSF WIND UPLIFT, INTERIOR AND EXTERIOR TURN HANDLES WITH PADLOCK HASPS.
- $\langle \overline{10} \rangle$  **PULL HANDLE**: INTERIOR PULL DOWN HANDLE, SAFETY YELLOW POWDER COAT

## NOTES:

- -WHEN INSTALLING ON A PITCHED ROOF UP TO 7:12, THE HINGE SIDE(LENGTH) MUST BE PARALLEL TO THE SLOPE.
- WIDTH X LENGTH DIMENSIONS ARE MEASURED INSIDE CURB TO INSIDE CURB. THE WIDTH IS HINGE TO LATCH AND LENGTH IS HINGED SIDE.

ROOF HATCH SIZE 30" (WIDTH) x 54" (LENGTH) CLEAR OPENING 23 1/8" (WIDTH) x 53 1/2" (LENGTH)

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

	PROJECT:							
	ARCHITECT:							
	CONTRACTOR:							
QTY:								
	PART:				BA3054			
	<b>babcock</b> davis  9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: BRHUA30X54S1T Roof Hatch Personnel II, 30x54, S Dr, Alum, Mill, Sngl Wall Curb			
		NAME	DATE	SIZE	DWG. NO	).		REV
	DRAWN	SGS	04/01/15	Α	BA3054			-
	RELEASED	IMT	04/01/15	WE	IGHT: 79.5	lbs	SHEET 1	OF 2

