

NOTES:

В

1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.078" (1.98mm) THICK

2. CLASS A FIRE RATING, TESTED TO ASTM E84

3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.062" (1.57mm) THICK

4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT

- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- 6. END CAP: #BCRVS4C-EC, OUTSIDE CORNER: #BCRVS4C-OC, 135 DEG OUTSIDE CORNER: #BCRVS4C-OC135, INSIDE CORNER: #BCRVS4C-IC, SPLICE KIT: #BCRVS4C-SK
- 7. FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

	PROJECT:						
	ARCHITECT:						
	CONTRACTOR:						
5,	babcock davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: 4" VINYL CRASH RAIL SURFACE MOUNT 1/8" CUSHION, CONTINUOUS RETAINER		
		NAME	DATE	SIZE	DWG. NO.		REV
	DRAWN	MDS	24APR13	Α		BCRVS4C-C125	A
	RELEASED	PGE	01MAY13	WE	IGHT: 1.03 lb	s/ft	SHEET 1 OF 1

QUANTITY

COLOR

2

1