

NOTES:

В

- 1. PROFILE: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.100" (2.54mm) THICK
- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM RETAINER, NOMINAL 0.080" (2.03mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. VINYL CRASH RAIL LENGTH: PROVIDED IN 20' CONTINUOUS SECTIONS
- 6. END CAP: #BCRVS8C-EC, OUTSIDE CORNER: #BCRVS8C-OC, 135 DEG OUTSIDE CORNER: #BCRVS8C-OC135, INSIDE CORNER: #BCRVS8C-IC, SPLICE KIT: #BCRVS8C-SK
- FASTENERS AND PARTITION COMPONENTS PROVIDED BY OTHERS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

	PROJECT: ARCHITECT: CONTRACTOR:							
5,	babcock davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: 8" VINYL CRASH RAIL SURFACE MOUNT CONTINUOUS RETAINER			
		NAME	DATE	SIZE	DWG. NO.			REV
	DRAWN	MDS	23APR13	Α	E	BCRVS8C		Α
	RELEASED	PGE	01MAY13	WE	IGHT: 2.25 lbs/ft		SHEET 1	OF 1