



COLOR

В

LENGTH

**QUANTITY** 

NOTES:

В

1. **PROFILE**: HIGH IMPACT VINYL ACRYLIC EXTRUSION LOCKED IN PLACE, NOMINAL 0.100" (2.54mm) THICK

- 2. CLASS A FIRE RATING, TESTED TO ASTM E84
- 3. RETAINER: CONTINUOUS 6063 T-5 ALUMINUM, NOMINAL 0.060" (1.52mm) THICK
- 4. **EXTRUSION**: PEBBLE GRAIN FINISH WHICH CONTAINS EPA REGISTERED MICRO-CHEK ANTIMICROBIAL AGENT
- 5. MAXIMUM LENGTH: VINYL CORNER GUARDS 20'
- 6. **HARDWARE**: #6 X 1-5/8" DRYWALL SCREWS INCLUDED
- PARTITION COMPONENTS PROVIDED BY OTHERS. FINISHED LENGTH INCLUDES END CAPS.

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

ŀ	PROJEC	CT:				
ARCHITECT:						
CONTRACTOR:						
<b>babcock</b> davis  9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: DOOR FRAME GUARD 2 11/16" X 2 11/16", 1 1/4" RADIUS		
	NAME	DATE	SIZE	DWG. NO.		REV
DRAWN	MDS	05SEP12	Α		BDGV26875	A
RELEASED	PGE	19OCT12	WE	IGHT: 4.31 lb	s/ft	SHEET 1 OF 1

2

1