

SPECIFICATIONS:

(†) DOOR:
316 SST, 3/16" DIAMOND PLATE, BEAD BLAST FINISH WITH A
LIVE LOAD OF 300 PSF WITH A MAX SPAN DEFLECTION OF 1/150

(†) DRAINAGE COUPLING: 1-1/2"

(8) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

(9) ANCHOR: 4" CONCRETE ANCHOR STRAPS PROVIDED

 $\langle \overline{2} \rangle$ FRAME:

316 SST, 3/16" FORMED SMOOTH PLATE, BEAD BLAST FINISH

(3) HINGES: TYPE 316 STAINLESS STEEL

(4) SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND

OUTSIDE REMOVABLE HANDLE

(5) COUNTER-BALANCE SPRING:

ENCLOSED, TYPE 17-7 SST SPRING

(6) HOLD-OPEN ARM:

TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP HANDLE

(7) DRAINAGE COUPLING: 1-1/2"

(8) FLUSH TYPE PLUG SEAL: TYPE 316 STAINLESS STEEL

FLOOR DOOR SIZE:

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT:						
ARCHITECT:						
CONTRACTOR:						
QTY:						
PART#:						
babcock davis 9300 73rd Avenue North, Brooklyn Park, MN 55428				TTLE: Floor Door, Drainable Series, Sngl Dr, 316 SST Hdw, 316 SST, Bead Blast, Pedestrian, Cast- In Anchors, Slam Latch Removbl L Hdl		
	NAME	DATE	SIZE	DWG. NO. Babcock FD BFDDPV_X_SWL ShpDr		REV
DRAWN	BES	8/3/2018	Α			A
RELEASED	TR	8/3/2018	WE	IGHT:	SHEET 1	OF 2

