







SPECIFICATIONS:

В

- $\langle 1 \rangle$ **BASE**: CHARCOAL CAST IRON
- $\langle 2 \rangle$ **ABRASIVE**: SILICON CARBIDE ABRASIVE ,CROSSHATCH PATTERN 1/32" THICK
- 3. FINISH: BLACK PAINT
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **LENGTH:** 5'6" MAXIMUM
- 6. WING ANCHORS: STANDARD FOR POURED CONCRETE **APPLICATIONS**

QTY

	PROJECT: ARCHITECT: CONTRACTOR:						
	QTY:						
	PART#:				BSTCI-C3W		
	babcock davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Stair Tread, Cast Series 3", Cast Iron Crosshatch		
					Short Nosing for Concrete, Wing	g Anchor	
		NAME	DATE	SIZE			REV
	DRAWN	SJB	3/31/11	Α	BSTCI-C3W		Α
	RELEASED	PE	3/31/11	WE	IGHT: 3.25 LB/FT	SHEET 1 (OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.