





## **SECTION A-A**

## SPECIFICATIONS:

В

- (1) COVER: ALUMINUM EXTRUSION WITH 11GA ALUM RETAINER TO WITHSTAND A LIVE LOAD OF 40 PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) TRANSLUCENT MATERIAL: POLYCARBONATE MULTI-WALL
- (3) CURB AND COUNTERFLASH W/ EZ TAB: 11 GAUGE ALUMINUM
- 4 FINISH: COVER- MILL CURB- MILL
- (5) GAS SPRING WITH DAMPER: DESIGNED TO OPEN AGAINST A 10PSF SNOW LOAD IN NOT LESS THAN 2 SECONDS
- (6) HOLD OPEN ARM: LOCK COVER IN FULLY OPEN POSITION ZINC PLATED STEEL
- (7) LATCH: ZINC PLATED ROTARY LATCH ASSEMBLY DESIGNED TO HOLD COVERS CLOSED AGAINST 90 PSF WIND UPLIFT ZINC PLATED STEEL LATCH STRIKERS ON COVERS

- 8 HINGES: ZINC PLATED STEEL WITH STAINLESS STEEL HINGE PINS
- 9 INSULATION:POLYISOCYANURATE IN COVER AND AROUND CURB PERIMETER, R-VALUE 6
- (10) GASKET: ADHESIVE BACKED EPDM RUBBER EXTRUSION
- (1) THERMAL RELEASE MECHANISM: VENT COVERS OPEN THERMALLY BY HEAT AT FUSIBLE LINK TEMPERATURE ""F
- (2) MANUAL OPENING: VENT COVERS OPEN WITH INTERNAL AND EXTERNAL MANUAL PULL HANDLE, 1/16" DIA SST CABLE

SMOKE VENT SIZE (WIDTH) x (LENGTH)

EFFECTIVE VENTING AREA , 0% SQFT

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.



F	PROJEC	CT:						
A	RCHITE	CT:						
СО	NTRAC	TOR:						
	QTY:							
PART#:				BSVLA	Х	D1	N	R
	3rd Aver	ckda	vis	TITLE: Smoke Vent, LightMAX Series Aluminum, Dbl Dr, Single Wall Curb Non-Electrical				
	NAME	DATE	SIZE	DWG. NO				REV
DRAWN	-	05/04/11	Α		BSVLA_>	X_D1N _R		-
RELEASED	DS	05/04/11	WEIGHT: VARIES SHEET					OF 2

ROUGH OPENING LENGTH FUSIBLE LINK ROUGH **OPENING** WIDTH **SPACING VARIES** 8"-15" Ø9/32" TYP Ø5/8" TYP -INSULATION-2 1/2" TYP 3 1/2" TYP SMOKE VENT COVER OPENS WHEN ACTIVATED BY: **A. THERMAL RELEASE MECHANISM:** RELEASED BY HEAT WITH A UL LISTED FUSIBLE LINK AT TEMPERATURE °F **DETAIL D OPTIONS:** 165 °F, 212 °F, 280 °F, 350 °F, 360 °F, 370 °F, 386 °F, 450 °F

— CONCRETE/WOOD/OTHER MATERIAL PROVIDED BY OTHER NIC

B. MANUAL OPENING: RELEASED BY EXTERNAL AND INTERNAL PULL CABLES WITH HANDLES AND 5FT OF INTERNAL CABLE PROVIDED

## SMOKE VENT COVER CLOSED MANUALLY FROM ROOFTOP

		3rd Aver	ckda	vis	TITLE: Smoke Vent, LightMAX Series Aluminum, Dbl Dr, Single Wall Curb Non-Electrical			
		NAME		SIZE	DWG. NO.		REV	
HF [	DRAWN	-	05/04/11	Α	BSVLA_X_D1N _R		-	
	RELEASED	DS	05/04/11	WE	IGHT: VARIES	SHEET 2 (	OF 2	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

2

**SECTION C-C**