babcockdavis®

Concealed

HINGED ACCESS DOOR

Designed for both ceiling and wall applications, the GFR panel can be used anywhere a locked door is required but style is still of utmost importance. The seamless design of these access doors blend into the surrounding drywall for a clean, upscale appearance.

FEATURES

ECO FRIENDLY These panels contain a 70% post-consumer recycled glass content for a truly GREEN product.

OPTIONAL LOCKS Constructed with European style hinges and choice of screwdriver cam latch or keyed cam lock.

CORNER OPTIONS Standard and custom sizes available in radius or square corners.

DETAILS

DOOR Gypsum Fiber Reinforced

FRAME Gypsum Fiber Reinforced

DOOR SHAPE Radius Corner or Square Corner

SIZE
- Min: 6 inches by 6 inches
- Max: 30 inches by 30 inches

INSTALLATION Wall or Ceiling

FLANGE Drywall

HINGE European

FINISH Unfinished Gypsum, Natural Gypsum White

ORDER GUIDE

BASE	DOOR SHAPE	LATCH		WIDTH	X	HEIGHT	APPLICATION
BGFR			—		**X**		
	R Radius Corner **S** Square Corner	**C** Screwdriver Cam Latch **L** Keyed Cam Lock		Standard Sizes (in.) 12" x 12" 16" x 16" 18" x 18" 24" x 24" 30" x 30"			**C** Ceiling Application **W** Wall Application

Rough opening is door size + 6 inches.
Additional sizes available, call for more information.

FINISH

Natural Gypsum White

DOOR SHAPE



Radius Corner

Square Corner

LATCHES

Screwdriver Cam Latch

Keyed Cam Lock