

Drainable

FLOOR DOOR, H20

The H20 Drainable Floor Door is designed for infrequent, off street traffic in exterior or high moisture areas when liquid flow into the door is a concern. The frame is constructed with a gutter channel for water runoff into a drainage system.

FEATURES

VEHICLE LOAD Designed for exterior/wet environments and tested for H20 wheel load for infrequent, off-street traffic.

DRAINABLE FRAME Constructed with a gutter channel frame and drain hole for liquid removal.



DETAILS

LOAD H20 wheel load

MATERIAL Aluminum: 1/4 inch, mill finish with gray primer on exterior frame

COVER Diamond tread plate

FRAME Drainable gutter frame with integral 1 inch anchor flange, EDPM gasket and 1-1/2 inch drain coupling

INSTALLATION Cast-In

SPRING Enclosed coil, Type 17-7 Stainless Steel

HINGES Heavy duty Type 316 Stainless Steel

HOLD OPEN ARM Type 316 Stainless Steel automatic hold open arm locks cover in open position

LATCH Slam latch Type 316 Stainless Steel with inside lever handle, includes removable threaded plug and key


OPTIONS Padlock Hasps, Locks, Finishes, Safety Grates, Safety Nets, Safety Rails, Skirting

MATERIALS



Aluminum

FRAME



Gutter Frame
Cast-In

ORDER GUIDE

MODEL	WIDTH	X	LENGTH	COVER	FL
BFDDHA		X			FL
	Standard Sizes (W x L)			S Single Leaf	
	Single Leaf	Double Leaf		D Double Leaf	
	24" x 24"	48" x 48"			
	30" x 36"	48" x 72"			
	36" x 36"	60" x 60"			
	42" x 42"				

Additional sizes available, call for more information.