

FRAME Welded Aluminum

- Min: 8 inches by 8 inches
- Max: 40 inches by 40 inches

**INSTALLATION** Ceiling or Wall

**LATCH** Push Latch **HINGE** Welded Pin

FINISH Mill

## **ORDER GUIDE**

	BASE	SE APPLICATION		WIDTH X LENGTH		LENGTH	OPTIONS		INFILL
	RG				Х			_	
		В	STB Pin Hinged	Standard Sizes (W x L)		(W x L)	<b>c</b> Screwdriver Cam Latch		<b>500</b> ½" drywall
		BR	Removable Door	8" x 8" 16 12" x 12" 20	.6" x 16" 24" x 24"	<b>D</b> Double Door		<b>625</b> %" drywall	
		Т	Tile		!0" x 2	10"	L Key Operated Cam Lock		



# Drywall

## **ACCESS DOOR**

The Drywall Access Door comes with standard ½ inch or ½ inch drywall installed in the door pan. Available in five standard sizes and three door styles for various application requirements.

## **FEATURES**

**PUSH LATCHING DOOR** Once installed, this door gives the desired appearance architects look for. The door quickly and easily opens and closes with the magnetic push-catch latch.

**SAFETY CORD** For overhead applications, this safety cord supports the door while opening the unit.

## **APPLICATION**







STB Pin Hinge

**OPTIONS** 

1





Key Operated Cam Lock



Door



## Recessed

## **ACCESS DOOR**

The non-rated Recessed Access Door provides access through openings in wall or ceiling surfaces. This door is designed to receive 5% inch drywall to match the surrounding surfaces.

## **DETAILS**

DOOR 16 gauge Steel FRAME 16 gauge Steel

- Min: 6 inches by 6 inches
- Max: 24 inches by 36 inches

**INSTALLATION** Wall and Ceiling

FLANGE None, Drywall Bead or Plaster Bead

**HINGE** Concealed Pin PAN DEPTH 5/8 inch

**FINISH** White Powder Primer Coat

## **ORDER GUIDE**



Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information. Touch Latch Doors are available in sizes 8" x 8" to 24" x 36".