

Entrance Flooring Systems - 12 48 16

eleGRIL[®] Stainless Steel Rigid Grates Models BGE38, BGE58, BGE98

| LEED Category | Credit | Details | Possible Points | Product/Material Detail |
|--|--------|--|---------------------------|--|
| Material and Resources (MR) | 4 | Recycled Content: Post-consumer + ½ Pre-consumer content | 1 to 2 possible points | All Models: contain a minimum of 18% pre-consumer recycled content and 72% post-consumer recycled content |
| | 5 | Regional Material: Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site | 1 to 2 possible points | Not applicable. Extraction Point is not within 500 miles of manufacturing. Final Packaging Facility Location: Brooklyn Park, MN 55428 |
| Indoor Environmental Quality (IEQ) | 4.1 | Low-Emitting Materials—Adhesives and Sealants | 1 possible point | Not applicable. |
| | 4.2 | IE Q Credit 4.2: Low-Emitting Materials— Paints and Coatings | 1 possible point | Not applicable. |
| | 4.3 | Low-Emitting Materials—Flooring Systems All carpet installed in the building interior must meet the testing and product requirements of the Carpet and Rug Institute Green Label Plus1 program. All carpet adhesive must meet the requirements of IEQ Credit 4.1: Adhesives and Sealants, which includes a volatile organic compound (VOC) limit of 50 g/L. | 1 possible point | Not applicable. Product does not require adhesives or sealants in the field. |
| | 5 | Indoor Chemical and Pollutant Source Control: Employ permanent entryway systems at least 10 feet long in the primary direction of travel to capture dirt and particulates entering the building at regularly used exterior entrances. Acceptable entryway systems include permanently installed grates, grill s and slotted systems that allow for cleaning underneath. Roll-out mats are acceptable only when maintained on a weekly basis by a contracted service organization. | 1 possible point | Meets the requirement if product is at least ten (10) feet in the traffic direction and the product is properly maintained. |