

# Safety Railings

## FALL PROTECTION

Babcock-Davis' OSHA compliant Safety Railing is an ideal solution to provide a permanent means of fall protection for new and retrofit applications. The safety railing permanently mounts to the floor around an existing floor door or opening.

### DETAILS

**MATERIAL** 1-1/4 inch ID (1.66 inch OD) Schedule 40 pipe

**FITTINGS** Cast aluminum alloy with set screw hold

**HARDWARE** Hex head bolts 3/8 inch - 16 x 3/4 inch zinc plated steel

### EXIT

- Self Closing Gate: Galvanized steel 1-1/4 inch tubular steel self closing with coil spring
- Chain: 3/16 inch zinc plated steel link chain with spring clip ends

**COMPLIANCE** OSHA 29 CFR1910.23 guarding floor and wall openings and holes

**SIZES** Industry standard and custom sizes available



### ORDER GUIDE

BASE	WIDTH	X	LENGTH	INSTALL
<b>SRTG</b>		<b>X</b>		
	Standard Sizes (W x L)			
	30" x 18"			<b>F</b> Front Exit
	30" x 24"			<b>S</b> Side Exit (Single Leaf Door)
	36" x 30"			<b>D</b> Side Exit (Double Leaf Door)
	36" x 36"			
	48" x 48"			<b>C</b> Chain
				<b>G</b> Self-Closing Gate

# Ladder Safety Post

## FALL PROTECTION

The Safety Post is designed in compliance to OSHA to extend 42 inches above a landing platform to provide safe ladder access through a roof hatch. The spring assisted telescoping design mounts to the top two rungs of a fixed vertical ladder.

### DETAILS

**MATERIAL** 1-1/2 inch by 1-1/2 inch by 1/8 inch high strength square tubing with a pull up loop provided at the upper end to facilitate raising of post

- Rail: Extruded aluminum 6061 T6
- Netting: Nylon webbing
- Rings: Aluminum alloy

**FINISH** Powder coat (steel), Mill (aluminum) or 2B Matte (stainless steel)

**FITTINGS** Cast aluminum alloy with set screw hold

**BALANCING SPRING** Stainless steel constant force spring

**HARDWARE** T316 Stainless Steel



### ORDER GUIDE

MODEL	MATERIAL	FINISH
<b>BSPY</b>	Steel	Powder Coat, Yellow
<b>BSPG</b>	Steel	Hot Dip Galvanized
<b>BSPA</b>	Aluminum	Mill
<b>BSPS</b>	Stainless Steel	Mill