

ABC DRY CHEMICAL



Finish: Glossy red polyester coated steel
Mounting: Wall bracket

Agent Base: Ammonium Phosphate
Fire Class: A, B, C Fires

Pressure: 195 P.S.I

MOUNTING BRACKETS (optional)

QTY	STEEL	NOMICAL CAPACITY	UL RATING	FM APPROVED	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	DISCHARGE TYPE
	BEX-3002	2-1/2 Lbs.	1A:10B:C	No	14-3/4"	3"	9'-15'	Nozzle
	BEX-3005	5 Lbs.	2A:10B:C	No	15-1/4"	4-1/4"	12'-18'	Hose
	BEX-3005-3	5 Lbs.	3A:40B:C	No	15-1/4"	4-1/4"	12'-18'	Hose
	BEX-3006	6 Lbs.	3A:40B:C	Yes	16"	5"	15'-21'	Hose
	BEX-3010	10 Lbs.	4A:80B:C	No	20"	5"	15'-21'	Hose
	BEX-3020	20 Lbs.	20A:120B:C	No	23-1/4"	7"	15'-21'	Hose

QTY	MODEL	FITS SIZE
	BEX-3901	5 Lbs.
	BEX-3902	6 Lbs.
	BEX-3903	10 Lbs.
	BEX-3904	20 Lbs.
	BEX-3909	5, 6, 10 Lbs.
	BEX-3910	20 Lbs.

KITCHEN CLASS "K"



Finish: Stainless Steel
Mounting: Wall bracket

Agent Base: Potassium Acetate Solution
Fire Class: K Fires

MOUNTING BRACKETS (optional)

QTY	MODEL	NOMICAL CAPACITY	UL RATING	FM APPROVED	HEIGHT	CYLINDER DIAMETER	OVERALL WIDTH	RANGE OF STREAM	DISCHARGE TYPE
	BEX-3260	1.4 Gal.	2A:K	No	19"	7"	9"	10'-12'	Hose & Nozzle
	BEX-3262	2-1/2 Gal.	2A:K	No	24-1/2"	7"	9"	10'-12'	Hose & Nozzle

QTY	MODEL	FITS SIZE
	BEX-3904	2-1/2 Lbs.

HALOTRON 1



Finish: Glossy red polyester coated steel
Mounting: Wall bracket

Agent Base: HydroChloroFluoro-Carbon
Fire Class: A, B, C Fires

Pressure: 125 P.S.I

MOUNTING BRACKETS (optional)

QTY	STEEL	NOMICAL CAPACITY	UL RATING	FM APPROVED	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	DISCHARGE TYPE
	BEX-3101	1.4 Lbs.	1B:C	No	10"	2-7/8"	6'-8'	Nozzle
	BEX-3102	2-1/2 Lbs.	2B:C	No	14-3/4"	3"	6'-10'	Nozzle
	BEX-3105	5 Lbs.	5B:C	No	15-1/4"	4-1/4"	9'-15'	Nozzle
	BEX-3111	11 Lbs.	1A:10B:C	No	21-1/2"	6"	9'-15'	Hose & Nozzle
	BEX-3115	15-1/2 Lbs.	2A:10B:C	No	21-1/2"	6"	12'-18'	Hose & Nozzle

QTY	MODEL	FITS SIZE
	BEX-3901	5 Lbs.
	BEX-3909	5, 6, 10 Lbs.

BC DRY CHEMICAL



Finish: Glossy red polyester coated steel
Mounting: Wall bracket

Agent Base: Sodium Bicarbonate
Fire Class: B, C Fires

Pressure: 195 P.S.I

MOUNTING BRACKETS (optional)

QTY	STEEL	NOMICAL CAPACITY	UL RATING	FM APPROVED	HEIGHT	CYLINDER DIAMETER	RANGE OF STREAM	DISCHARGE TYPE
	BEX-3302	2-1/2 Lbs.	10B:C	No	14-3/4"	3"	9'-15'	Nozzle
	BEX-3305	5 Lbs.	10B:C	No	15-1/4"	4-1/4"	12'-18'	Nozzle
	BEX-3305-3	5-1/2 Lbs.	40B:C	No	15-1/4"	4-1/4"	12'-18'	Hose
	BEX-3306	6 Lbs.	40B:C	Yes	16-3/4"	5"	15'-21'	Hose
	BEX-3310	10 Lbs.	60B:C	No	20"	5"	15'-21'	Hose
	BEX-3320	20 Lbs.	120B:C	No	23-1/4"	7"	15'-21'	Hose

QTY	MODEL	FITS SIZE
	BEX-3901	5 Lbs.
	BEX-3902	6 Lbs.
	BEX-3903	10 Lbs.
	BEX-3904	20 Lbs.
	BEX-3909	5, 6, 10 Lbs.
	BEX-3910	20 Lbs.

CARBON DIOXIDE



Finish: Glossy red polyester coated steel
Mounting: Wall bracket

Agent Base: Carbon Dioxide
Fire Class: B, C Fires

Pressure: 735 P.S.I

MOUNTING BRACKETS (optional)

QTY	STEEL	NOMICAL CAPACITY	UL RATING	FM APPROVED	HEIGHT	CYLINDER DIAMETER	OVERALL WIDTH	RANGE OF STREAM	DISCHARGE TYPE
	BEX-3405	5 Lbs.	5B:C	No	17-3/4"	5-1/4"	8-1/4"	3'-8'	Horn
	BEX-3410	10 Lbs.	10B:C	No	24"	7"	12"	3'-8'	Hose & Horn
	BEX-3415	15 Lbs.	10B:C	No	30"	7"	12"	3'-8'	Hose & Horn
	BEX-3420	20 Lbs.	10B:C	No	30"	8"	12"	3'-8'	Hose & Horn

QTY	MODEL	FITS SIZE
	BEX-3903	5 Lbs.
	BEX-3904	10, 15 Lbs.
	BEX-3905	20 Lbs.
	BEX-3909	5 Lbs.