

Lume-A-Lite™

PHOTOLUMINESCENT SIGNS

Babcock-Davis' new Lume-A-Lite Photoluminescent Signs provide a non-electric luminous egress routing system that is easily followed in the case of power loss in an emergency situation. The material has been tested to UL 1994 and ASTM E2073 test standards and meets current IBC, IFC, and NFPA code requirements.

FEATURES

SAFE EGRESS The glow-in-the-dark photoluminescent signage provides directions for a safe exit route

VISIBILITY Exit signs are rated for 100 foot visibility with 90 minute emergency illumination.

EASY INSTALL The egress signs come with either self-adhesive tabs or can be installed with a mounting bracket.




DETAILS

COLOR Photoluminescent

MOUNTING Surface or Mechanical

COMPLIANCE UL 1994, ASTM E2073, 2015 IBC/IFC 1023 and 1025



MODELS

MODEL	WIDTH	DESCRIPTION
BEM-SE-KIT		Low Level Exit Sign/Door Kit, Adhesive
BEM-SR_-8X8	8" x 8"	Running Man Sign, Self-Adhesive
BEM-DLM-4X4	4" x 4"	Door Latch Marking, Self-Adhesive
BEM-SRA_-8X4.5	8" x 4-1/2"	Running Man with Arrow, Adhesive Tab
BEM-SREFA_-8X11	8" x 11"	Running Man Final Exit, Adhesive Tab
BEM-SRE_-13X4.5	13" x 4-1/2"	Running Man Exit, Adhesive Tab
BEM-SRLA_-16X7	16" x 7"	Lobby Exit with Arrow, Adhesive Tab
BEM-SREA_-8X9	8" x 9"	Running Man Arrow Exit
BEM-SFI-13X18	13" x 18"	Floor ID Sign, Mech. Fastened or Adh. Tab
BEM-SLE100_1-15.5X8.75	16" x 9"	100' 1-Sided Exit Sign, Mech. Fastened
BEM-SE100_2-15.5X8.75	16" x 9"	100' 2-Sided Exit Sign, Mech. Fastened
BEM-SNE-5.5X6.5	5-1/2" x 6-1/2"	Not an Exit Sign

Additional options available, call for more information.

SIGNS



Door Kit



Running Man



Door Latch Marking



Running Man with Arrow



Running Man Final Exit



Running Man Exit



Lobby Exit with Arrow



Running Man Arrow Exit



Floor ID



1-Sided Exit Sign



2-Sided Exit Sign



Not an Exit Sign