

Perimeter

GUARDRAIL FALL PROTECTION

The OSHA compliant Permanent Guardrail system's unique bracket installs under the drip edge, coping cap, gravel stop or gutter system without penetrating the roofing system and allows for retro fit installations.

FEATURES

PERMANENT MOUNT The edge mounted guardrail system does not penetrate the roof membrane and installs under the coping and roof flashing.

EASY INSTALLATION The posts and rails are easy to assemble and install.

COORDINATING COLORS The system comes with a standard powder coat finish that is available in a wide range of colors to match your building's exterior.



DETAILS

MATERIALS

- Post and Bracket Assembly: Steel, 1-1/4 inch ID (1.66 inch OD) Schedule 40 pipe
- Horizontal and Corner Rails: 1-5/8 inch by .065 inch Steel

FINISH Powder Coat

STRUCTURAL FASTENERS

- Wood: RSS structural screws
- Concrete: Caliburn PH concrete pan head screw

RAIL FASTENERS 3/8 inch - 16 x 1 inch zinc plated steel

COMPLIANCE OSHA 29 CFR 1910.28 and 1910.29

STANDARD MODELS

MODEL	DESCRIPTION	DIMENSION	MATERIAL + FINISH
BFP-GRPLG	Edge Mount Post	42"	Steel, Powder Coat
BFP-GRF60	Fixed Rail*	5'	Steel, Powder Coat
BFP-GRF96	Fixed Rail*	8'	Steel, Powder Coat
BFP-GRF118	Fixed Rail*	9'- 10"	Steel, Powder Coat
BFP-GRA43	Adjustable Rail*	2'-5" to 3'-9"	Steel, Powder Coat
BFP-GRA70	Adjustable Rail*	3'-9" to 5'-10"	Steel, Powder Coat
BFP-GRA120	Adjustable Rail*	5'-10" to 10'	Steel, Powder Coat
BFP-GRC12	Corner Rail*	12"	Steel, Powder Coat

*Note: Rails and corners are sold in sets of 2.

