

# Renovation

## ACCESS DOOR

The Babcock-Davis Renovation Access Door is a lighter gauge alternative to the Architectural Door. The panel features an industry-leading design to provide superior durability and functionality.

### DETAILS

**DOOR** 20 gauge Steel

**FRAME** 20 gauge Steel

### SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

**INSTALLATION** Ceiling or Wall

**FLANGE** 1 inch Exposed

**HINGE** Concealed Spring Button

**PAN DEPTH** 1/2 inch

**FINISH** White Powder Coat



### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BE</b>				<b>X</b>		
	<b>T</b> 1 inch Flange	<b>C</b> Screwdriver Cam Latch <b>L</b> Key Operated Cam Lock	<b>Standard Sizes (W x L)</b> 6" x 6" 8" x 8" 10" x 10" 12" x 12" 12" x 18" 12" x 24" 14" x 14" 16" x 16"	16" x 20" 18" x 18" 18" x 24" 20" x 30" 22" x 22" 22" x 30" 24" x 24" 24" x 30"	24" x 36" 24" x 48" 30" x 30" 30" x 36" 32" x 32" 36" x 36"	<b>B</b> Galvannealed <b>G</b> Gasketing

*Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.*

# Recessed

## ACCESS DOOR

The non-rated Recessed Access Door provides access through openings in wall or ceiling surfaces. This door is designed to receive 5/8 inch drywall inlay to match the surrounding surfaces.

### DETAILS

**DOOR** 16 gauge Steel

**FRAME** 16 gauge Steel

### SIZE

- Min: 6 inches by 6 inches
- Max: 24 inches by 36 inches

**INSTALLATION** Ceiling

**FLANGE** None, Drywall Bead or Plaster Bead

**HINGE** Concealed Pivoting Rod

**PAN DEPTH** 5/8 inch

**FINISH** White Powder Coat or None



### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BR</b>				<b>X</b>		
	<b>A</b> No Flange <b>P</b> Plaster Bead <b>W</b> Drywall Bead	<b>C</b> Screwdriver Cam Latch <b>L</b> Key Operated Cam Lock <b>M</b> Mortise Lock (1-1/8") Prep	<b>Standard Sizes (W x L)</b> 8" x 8" 12" x 12" 16" x 16" 18" x 18"	20" x 30" 24" x 24" 24" x 30" 24" x 36"		<b>B</b> Galvannealed <b>G</b> Gasketing <b>S</b> Type 304 Stainless Steel

*Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.  
\*Ceiling application only.*