



SPECIFICATIONS

D

В

RAILS, POSTS: 6061 T6 ALUMINUM ALLOY 1 1/4" I.D. SCH 40

CHAIN: ZINC PLATED STEEL WITH CLIPS ON BOTH ENDS

COUNTERFLASH MOUNTING BRACKETS: 3/16" ZINC PLATED STEEL FASTENED TO STEEL BACKING PLATE, SLATE GRAY POWDER COAT

BOLTS: HEX HEAD BOLTS 3/8"-16 x 3/4" GRADE 5 ZINC PLATED

RAILING FITTINGS AND PLUGS: MANUFACTURER'S STANDARD CAST

WITH SET SCREW HOLD

FITS HATCH SIZES UP TO 36" X 30"

SRCA36X30FC **babcock**davis Safety Railings for Roof Hatch 36X30, Front Exit, Alum, Mill, Chains 9300 73rd Avenue North Brooklyn Park, MN 55428 SIZE DWG. NO. REV NAME DATE В DRAWN SJB TODAY SRCA36X30FC WEIGHT: Weight SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED. | RELEASED | DWO | 4/10/2018

8 7 6 5 4 3 2