



1" PHOTOLUMINESCENT INSERT

MODEL STSM-P3E-ECO

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PART
EPOXY, LOCKED INTO EXTRUDED CHANNELS



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT:			
ARCHITECT:			
CONTRACTOR:			
QTY:			
PART#:			
		TITLE: Stair Tread, Single Stage, 3 1/2" x 11" x 1/2" Ribs, Photoluminescent Insert, Short Tip Nose, Alum Extruded Anchor, 1" Photoluminescent Insert	
9300 73rd Avenue North Brooklyn Park, MN 55428			
NAME	DATE	SIZE	DWG. NO.
DRAWN	DKL	3/6/19	A
RELEASED	TR	3/6/19	WEIGHT:
Babcock BSTSM-P3E-ECO ShpDr			REV A
SHEET 1 OF 1			