

April 2026

RE: Sustainability Statement

Babcock-Davis certifies and provides the following information for use in achieving LEED v5 credit for specification of the following:

Product: SafeMAX™ Smoke Vents

Models: BSVSA, BSVSW, BSVSB

Final Assembly Location: Minneapolis, MN

LEED v5 Credit Contributions

Category: Materials and Resources

Credit: MRc3 – Low-Emitting Materials (2 Points Possible)

Babcock-Davis SafeMAX™ Smoke Vents consist of at least 94% powder coated, plated or anodized metals, which LEED considers inherently non-emitting sources of VOCs.

Category: Materials and Resources

Credit: MRc4 – Building Product Selection and Procurement (5 Points Possible)

Babcock-Davis has demonstrated achievement in two criteria areas for SafeMAX™ Smoke Vents:

- *Human Health:* A published, complete Health Product Declaration (HPD) is available for [SafeMAX™ Smoke Vents](#), with full disclosure of known hazards of all substances present at or above 1,000 ppm (0.1%) and Pre-Checked for LEED [Score: 1]
- *Circular Economy:* Babcock-Davis SafeMAX™ Smoke Vents are constructed primarily of Aluminum and/or Steel, with the following recycled content: [Score: Up to 1]
 - BSVSA (Aluminum Curb and Cover)
 - Minimum 81% Aluminum Alloy (40-80% pre-consumer; 10-30% post-consumer)
 - Minimum 13% Steel Alloy (default 25% post-consumer)
 - BSVSW (Steel Curb and Cover)
 - Minimum 96% Steel Alloy (default 25% post-consumer)
 - BSVSB (Steel Curb and Aluminum Cover)
 - Minimum 67% Steel Alloy (default 25% post-consumer)
 - Minimum 27% Aluminum Alloy (40-80% pre-consumer; 10-30% post-consumer)