NEW



babcockdavis®

Acoustical

ACCESS DOOR

The BAC Acoustical access door is designed for wall and ceiling openings where sound control is part of the project requirement. A keyed lift-and-turn compression latch draws the panel tightly against the gasket to control sound transmission around the perimeter.

FEATURES

STANDARD SIZES 12 inches by 12 inches to 48 inches by 48 inches. Custom sizes are available.

CERTIFICATION

- Tested to ASTM E1332, ASTM E90 and ASTM E413
- Rated to STC 64 and OITC 51 when installed according to manufacturer's instruction.

DETAILS

DOOR 20 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 12 inches by 12 inches
- Max: 48 inches by 48 inches

INSTALLATION Wall or Ceiling

FLANGE 1-inch Exposed

HINGE Continuous Piano Hinge

GASKET Closed Cell Neoprene

FINISH White Enamel Prime Coat or #4 Satin (Stainless Steel)

INSULATION 2-3/8 inch Acoustical

ORDER GUIDE

MODEL	WIDTH	X	LENGTH	OPTION
BAC		X		
	Standard Sizes 12" x 12" 16" x 16" 18" x 18" 24" x 24" 24" x 32"			**S** Stainless Steel, Type 304

Rough opening is door size + 3/8-inch.
Additional sizes available, call for more information.

MATERIALS



White Enamel Prime Coat



#4 Satin Stainless Steel

FLANGES



1-inch Flange

LATCHES



Keyed Lift and Turn Compression Latch