NEW

Clean Room

ACCESS DOOR

The Clean Room Access Door is ideal for applications where moisture or air movement is a consideration through walls or ceilings. Gasketing on all four sides ensures continuity of the seal and can be used on both interior and exterior applications.

FEATURES

CUSTOM SIZES Custom sizes are available, from 8 inches by 8 inches to 36 inches by 60 inches.

CERTIFICATION Tested in accordance with ASTM E283 and ASTM E331

DETAILS

DOOR 16 gauge Galvanneal Steel

FRAME 16 gauge Galvanneal Steel

SIZE

- Min: 8 inches by 8 inches
- Max: 36 inches by 60 inches

INSTALLATION Wall or Ceiling

FLANGE 3/4-inch Exposed

HINGE Continuous Stainless Steel Piano Hinge

GASKET Black, closed cell blended rubber; EPDM/Neoprene/SBR

FINISH Off-White Prime

CERTIFICATION ASTM E283 and ASTM E331

ORDER GUIDE

MODEL	LATCH	WIDTH	X	LENGTH	OPTION
BMNT			**X**		
	C Screwdriver Cam Latch **A** 1/4" Allen Key **L** Cylinder Lock Installed **M** Mortise Prep **TP** Non-Locking 2 Position Handle	**Standard Sizes** 8" x 8" 10" x 10" 12" x 12" 16" x 16" 18" x 18" 20" x 20" 24" x 24" 24" x 36" 30" x 30" 36" x 36"			**S** Stainless Steel, Type 304

Rough opening is door size.
Additional sizes available, call for more information.

MATERIALS

Off-White Prime Coat

#4 Satin (Stainless Steel)

FLANGES

3/4-inch Flange

LATCHES

Screwdriver Cam Latch

Hex Cam Latch

Key Operated Cam Lock

Mortise Lock Prep