

SPECIFICATIONS:


- ① **DOOR:** ALUMINUM 1/4" SMOOTH PLATE WITH 1" TILE EXTRUSION RECESS FOR FLOORING INFILL, MILL FINISH WITH A LIVE LOAD OF 250PSF WITH A MAX SPAN DEFLECTION OF L/150
- ② **FRAME:** ALUMINUM, 1/4" EXTRUSION
- ③ **HINGES:** TYPE 316 STAINLESS STEEL CONTINUOUS HINGE
- ④ **SLAM LATCH:** ZINC-PLATED STEEL WITH INSIDE HANDLE MECHANISM AND OUTSIDE REMOVABLE HANDLE
- ⑤ **COUNTER-BALANCE SPRING:** ENCLOSED, TYPE 17-7 SST SPRING
- ⑥ **HOLD-OPEN ARM:** TYPE 316 STAINLESS STEEL
OPTIONAL SELF-CLOSING MECHANISM






- ⑦ **ANCHOR:** 3/8" HOLES PROVIDED, BOLTS SUPPLIED BY OTHERS
- ⑧ **PLUG SEAL:** TYPE 316 STAINLESS STEEL

CERTIFICATION: 2-HOUR FIRE RATED, WARNOCK HERSEY LABELED AND TESTED TO NFPA 288: STD METHODS OF FIRE TEST OF HORIZONTAL FIRE DOOR ASSEMBLIES. MAX TEMPERATURE RISE OF 250F.

APPLICATION NOTE: FLOOR DOOR MUST BE KEPT DRY BEFORE, DURING, AND AFTER INSTALLATION. FOR DRY, INTERIOR INSTALLATION ONLY. NOT INTENDED FOR EXTERIOR OR WET ENVIRONMENTS.

FLOOR DOOR SIZE:

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:					
<div> babcockdavis</div> <div>9300 73rd Avenue North Brooklyn Park, MN 55428</div>			TITLE: FD, 2hr Fire Rated, 250 psf, Sngl Dr, Alum, 1/4" Smth Plt, 1" Pan, Mill, Angle Frame, Bolg-In, SST Spring Asst, 316 SST HDW, Slam Latch w/Hdl		
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BES		A	Babcock FD BFD FPA_X_SWL-BI-P1 ShpDr	
RELEASED	BES		WEIGHT:	SHEET 1 OF 2	



9300 73rd Avenue North
Brooklyn Park, MN 55428

TITLE: FD, 2hr Fire Rated, 250 psf,
, Sngl Dr, Alum, 1/4" Smth Plt, 1" Pan,
Mill, Angle Frame, Bolt-In,
SST Spring Asst, 316 SST HDW, Slam Latch w/Hdl

	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	BES		A	Babcock FD BFD FPA_X_SWL-BI-P1 ShpDr	
RELEASED	BES		WEIGHT:		

SHEET 2 OF 2