



HVAC ACCESS DOOR

HVAC access doors discreetly conceal HVAC systems in multifamily and hospitality buildings. The large doors provide easy access for service and repair of equipment.

FEATURES

INSULATED 1½-inch thick Linacoustic® duct liner provides superior acoustical and thermal performance.

RETURN AIR OPTIONAL Perforated return air to meet free air requirements.

GASKET OPTIONS EPDM reduces sound transmission and maintains air filtration.

CUSTOM SIZES Custom sizes are available, from 28 inches by 42 inches to 36 inches by 72 inches.

PREHUNG DOOR ALTERNATIVE Requires no additional hardware or trim. Reduce install time. Provides a sleek integrated finished look.

DETAILS

DOOR

- 20 gauge Steel
- Optional metal liner (20-gauge Steel)

FRAME 16 gauge Steel

SIZE

- Min: 28 inches by 42 inches
- Max: 36 inches by 72 inches

INSTALLATION Wall or Ceiling



FLANGE ¼ inch exposed; Drywall bead

HINGE Concealed Pin

FINISH White Powder Primer Coat

INSULATION 1½ inch Linacoustic Duct Liner

MATERIALS



White Powder
Primer Coat

FLANGES



1/4-inch Flange



Drywall Bead



LATCHES



Hex Cam Latch



Key Operated
Cam Lock



Pinned Hex
Cam Latch



Mortise
Lock Prep



Screwdriver
Cam Latch

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
BHVAC				X		
	T 1¼" Flange W Drywall Bead	H Hex Head Cam L Key operated Cam Lock P Pinned Hex Cam Latch M Mortise Lock (1½") Prep C Screwdriver Cam Latch	Standard Sizes 30" x 48" 32" x 60" 30" x 54" 32" x 66" 30" x 60" 32" x 72" 30" x 66" 34" x 48" 30" x 72" 34" x 54" 32" x 48" 34" x 60" 32" x 54" 36" x 72"			G Gasketing Installed P Perforated Door Q Metal Liner C Ceiling Kit

Rough opening is door size + ¼ inch minimum.

Additional sizes available, call for more information.

Linacoustic is a registered trademark of Johns Manville ©2024