



HVAC ACCESS DOOR



The HVAC Access Door is available in large sizes to provide easy access for service and repair of equipment,

FEATURES

INSULATED 1½-inch thick fiberglass insulation (Linacoustic) provides superior acoustical and thermal performance.

RETURN AIR Perforated return air to meet free air requirements.

GASKET OPTIONS EPDM Reduces sound transmission and maintains air filtration.

CUSTOM SIZES Custom sizes are available, from 28 inches by 42 inches to 36 inches by 72 inches.

DETAILS

DOOR

- 20 gauge Steel
- Liner option 20 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 28 inches by 42 inches
- Max: 36 inches by 72 inches

INSTALLATION Wall

FLANGE 1¼ inch Exposed

HINGE Concealed Pin

FINISH White Powder Coat

INSULATION 1½ inch Fiberglass

MATERIALS



White
Powder Coat

FLANGES



1¼-inch Flange


LATCHES



Screwdriver
Cam Latch



Key Operated
Cam Lock



Mortise
Lock Prep



Pinned Hex
Cam Latch



Hex Cam Latch

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
BHVAC			X		
	C Screwdriver Cam Latch	Standard Sizes			G Gasketing Installed
	L Key operated Cam Lock	30" x 48"	32" x 60"	34" x 66"	P Perforated Door
	P Pinned Hex Cam Latch	30" x 54"	32" x 66"	34" x 72"	N Liner
	M Mortise Lock (1-½" Prep)	30" x 60"	32" x 72"	36" x 48"	
	H Hex Head Cam	30" x 66"	34" x 48"	36" x 54"	
		30" x 72"	34" x 54"	36" x 60"	
		32" x 48"	34" x 60"	36" x 66"	
		32" x 54"		36" x 72"	

Rough opening is door size + 1/4 inch minimum.
Additional sizes available, call for more information.