babcockdavis®

Architectural

ACCESS DOOR

The Babcock-Davis Architectural Access Door is built with the architect in mind. Constructed with an industry-standard steel door, the design further improves on strength and aesthetics.

FEATURES

ANTI-FLEX FRAME Screws are inserted through our patent-pending Easy Install Tabs, firmly fitting the door to the wall without flexing the frame.

PAINLESS INSTALLATION When mounting screws are not required, quickly and easily install your new panel by bending our Easy Install Tabs over the drywall.

OPTIONAL STAINLESS STEEL The spot free design on the face of the door gives an aesthetically pleasing appearance.

DETAILS

DOOR
- BNT/BNW: 16 gauge Steel
- BNP: 14 gauge Steel
- 16 gauge Type 304 Stainless Steel

FRAME
- 16 gauge Steel
- 16 gauge Type 304 Stainless Steel

SIZE
Single Door
- Min: 6 inches by 6 inches
- Max: 24 inches by 72 inches or 48 inches by 48 inches

Double Door
- Min: 24 inches by 24 inches
- Max: 36 inches by 72 inches or 48 inches by 64 inches

INSTALLATION Ceiling or Wall

FLANGE 1 inch Exposed, Drywall Bead or Plaster Bead

HINGE Concealed Spring Button or Flush Continuous Piano

PAN DEPTH 1/2 inch

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
BN				**X**		
	T 1 inch Flange **W** Drywall Bead **P** Plaster Bead	**C** Screwdriver Cam Latch **L** Key operated Cam Lock **M** Mortise Lock (1-⅛") Prep **N** Knurled Knob Latch	**Standard Sizes** Single Door Only 6" x 6" 8" x 8" 10" x 10" 12" x 12" 12" x 18" 12" x 24" 14" x 14" 16" x 16" 16" x 20" 18" x 18" 18" x 24" 20" x 30" 22" x 22" 22" x 30" 24" x 24" 24" x 30" 24" x 36" 24" x 48" 30" x 30" 30" x 36" 32" x 32" 36" x 36"			**F14** 14 gauge Frame & Door **L** Louvered Door **S** Stainless Steel, Type 304 **D14** 14 gauge Door **D** Double Door

Double doors are available (Some options may not be available). Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.
Lead Time Average is 1-10 Days for standard sizes. Delivery time is additional.

OPTION



Double Door

MATERIALS

White Powder Coat

#4 Satin Stainless Steel

FLANGES

1 inch Flange

Drywall Bead



Plaster Bead

LATCHES

Screwdriver Cam Latch

Key Operated Cam Lock

Mortise Lock Prep

Knurled Knob

Download Drawings, CAD, Spec, and LEED documents at babcockdavis.com