



SPECIFICATIONS:

- (1) DOOR: ALUMINUM 1/4" DIAMOND PLATE MILL FINISH WITH A LIVE LOAD OF 300 PSF AND MAX SPAN DEFLECTION OF L/150
- (2) FRAME: ALUMINUM, 1/4" EXTRUSION, MILL FINISH
- (3) HINGES: TYPE 316 STAINLESS STEEL
- 4 SLAM LATCH: TYPE 316 STAINLESS STEEL WITH INSIDE LEVER HANDLE AND OUTSIDE REMOVABLE HANDLE
- (5) COUNTER-BALANCE SPRING: ENCLOSED, TYPE 17-7 SST SPRING
- (6) HOLD-OPEN ARM: TYPE 316 STAINLESS STEEL WITH RED VINYL GRIP **HANDLE**
- $\overline{\langle 7 \rangle}$ **ANCHOR:** 3/8" HOLES PROVIDED FOR BOLTING IN ON SITE

8 SAFETY GRATE:

ALUMINUM, 6" SERRATED RAILS WITH SAFETY ORANGE POWDER COAT, LIVE LOAD OF 300PSF, SST HINGES LOCK AND INTEGRAL PADLOCK HASP

(9) NUT-RAIL: ALUMINUM NUT-RAIL ON HINGE AND LATCH SIDES

THIS UNIT IS NOT AIR OR WATER TIGHT.

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: TITLE: **babcock**davis 9300 73rd Avenue North Brooklyn Park, MN 55428 NAME DATE SIZE DWG. NO. REV Α Α DRAWN SWS 3-31-17 PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED. THIS SHOP DRAWING MAY NOT BE AN ACTUAL REPRESENTATION OF THE FINAL PRODUCT. RELEASED TR WEIGHT: SHEET 1 OF 2 3-31-17

5

