

September 2025

RE: Sustainability Statement

Babcock-Davis certifies and provides the following information for use in achieving LEED v4.1 credit for the specification of our Aluminum Safety Railings.

Product: Aluminum Safety Railings
Models: BSGB, BSP, BSRC, BSRTAY, BSRV, BSRVAY

Manufacturing Information:

- Final Assembly Location: Minneapolis, MN
- Extraction point is not within 500 miles of manufacturing

LEED Credit Contributions

Category: Materials and Resources (MR)
Credit: Sourcing of Raw Materials (1-2 Points)

Recycled Content: Babcock-Davis Aluminum Safety Railings are constructed of the following materials:

- Minimum 57% Aluminum Alloy: suppliers estimate 5-80% (average 35%) total recycled content. Please contact us if you have specific requirements for recycled content.
- Minimum 40% Steel Alloy: LEED[®] allows a default value of 25% post-consumer recycled content. Steel used by Babcock-Davis may have higher recycled content, and may also include pre-consumer content. However, we have chosen to report this default value due to the variability of recycled content over time.

Category: Materials and Resources (MR)
Credit: Material Ingredients

Material Ingredient Reporting (1 Point): A published, complete Health Product Declaration (HPD) is available for [Babcock-Davis Aluminum Safety Railings](#), with full disclosure of known hazards of all substances present at or above 0.1% (1,000 ppm), in compliance with the Health Product Declaration Open Standard. Babcock-Davis Aluminum Safety Railings can therefore contribute one whole product to the 20 different permanently installed products required for this credit.

Category: Indoor Environmental Quality (EQ)
Credit: Low-Emitting Materials (Up to 3 Points)

Babcock-Davis Aluminum Safety Railings are constructed entirely of powder coated, plated or anodized metals, which LEED considers inherently non-emitting sources of VOCs.