



SPECIFICATIONS:

- $\overleftarrow{\text{1}}$ COVER: 11 GA (0.09") ALUM COVER STIFFENED TO WITHSTAND A LIVE LOAD OF 40PSF WITH A MAX DEFLECTION OF 1/150 OF THE SPAN
- (2) **LINER:** 18 GA (0.04") ALUM
- (3) CURB: 11 GA (0.09") ALUM, CURB COUNTERFLASH WITH EZ TABS
- 4 FINISH: MILL
- $\langle \overline{5} \rangle$ **HINGE**: PINTLE HINGE WITH STAINLESS STEEL HINGE PINS
- (6) SPRING: GAS SPRING WITH DAMPER FOR SMOOTH,
- CONTROLLED COUNTERBALANCED LIFT ASSISTANCE
- $\overline{\langle 7 \rangle}$ HOLD OPEN ARM: STEEL AUTOMATIC HOLD OPEN ARM LOCKS COVER IN FULLY OPENED POSITION WITH STEEL AUTOMATIC HOLD RED GRIP HANDLE RELEASE

- (8) LATCH: 2-PT ROTARY LATCH HOLDS COVER CLOSED AGAINST 20 PSF WIND UPLIFT. INTERNAL AND EXTERNAL TURN HANDLES WITH PADLOCK HASPS
- (10) GASKET: ADHESIVE-BACKED EPDM RUBBER EXTRUSION
- (11) PULL HANDLE: INTERIOR PULL DOWN HANDLE

ROOF HATCH SIZE: " (WIDTH) x " (LENGTH) **OPTIONS**

Stainless Steel Hardware

Double Wall Curb

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART: TITLE: **babcock**davis[®] 9300 73rd Avenue North Brooklyn Park, MN 55428 NAME DATE SIZE DWG. NO. Generic Babcock RH BRHEA_X_D_T ShpDr Α DRAWN

REV RELEASED SHEET 1 OF 2 WEIGHT:

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED. @2020 BABCOCK-DAVIS

