



SPECIFICATIONS:

- ① **BASE: 319 CAST ALUMINUM**
- ② **ABRASIVE: SILICON CARBIDE ABRASIVE , CROSSHATCH PATTERN 1/8" DEEP**
- 3. **FINISH: SAND CAST**
- 4. **POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS**
- 5. **LENGTH: 6" MINIMUM 6'-0" MAXIMUM**

| LENGTH ± 1/8 | QTY |
|--------------|-----|
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| | | | | | |
|---|------|---|--------------------|-----------|--------------|
| PROJECT: | | | | | |
| ARCHITECT: | | | | | |
| CONTRACTOR: | | | | | |
| QTY: | | | | | |
| PART#: | | BSTCA-C2C | | | |
| 9300 73rd Avenue North Brooklyn Park, MN 55428 | | TITLE: Stair Tread, Cast Series 2", Cast Aluminum Crosshatch Short Nosing for Concrete, Bolt Anchor | | | |
| | | | | | |
| | NAME | DATE | SIZE | DWG. NO. | REV |
| DRAWN | SJB | 3/31/11 | A | BSTCA-C2C | A |
| RELEASED | DWO | 3/31/11 | WEIGHT: 0.69 LB/FT | | SHEET 1 OF 1 |

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.