







SPECIFICATIONS:

- 1 BASE: 319 CAST ALUMINUM
- (2) ABRASIVE: SILICON CARBIDE ABRASIVE , CROSSHATCH PATTERN 1/8" DEEP
- 3. FINISH: SAND CAST
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. LENGTH: 6" MINIMUM 6'-0" MAXIMUM

| LENGTH ± 1/8 | QTY |
|--------------|-----|
| | |
| | |
| | |
| | |
| | |
| | |
| | |

| | F | PROJECT: | | | | | |
|--|------------------------------------|----------|-----------|------|---|--|------|
| | ARCHITECT: CONTRACTOR: QTY: PART#: | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | BSTCA-L4C | | |
| babcock davis 9300 73rd Avenue North Brooklyn Park, MN 55428 | | | nue North | vis | TITLE: Stair Tread, Cast Series 4", Cast Aluminum Crosshatch Long Nosing for Pan, Bolt Anchor | | |
| | | NAME | DATE | SIZE | DWG. NO. | | REV |
| | DRAWN | SJB | 3/31/11 | Α | BSTCA-L4C | | Α |
| | RELEASED | DWO | 3/31/11 | WE | IGHT: 1.59 LB/FT SHEET | | OF 1 |

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

2

1