







SPECIFICATIONS:

- 1 BASE: 319 CAST ALUMINUM
- (2) ABRASIVE: SILICON CARBIDE ABRASIVE, CROSSHATCH PATTERN 1/8" DEEP
- 3. FINISH: SAND CAST
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. LENGTH: 6" MINIMUM 6'-0" MAXIMUM

LENGTH ± 1/8	QTY

	PROJECT:									
	ARCHITECT: CONTRACTOR: QTY:									
	PART#:				BSTCA-P2C					
	babcock davis 9300 73rd Avenue North Brooklyn Park, MN 55428				TITLE: Stair Tread, Cast Series 2", Cast Aluminum Crosshatch Short Nosing for Pan, Bolt Anchor					
		NAME	DATE	SIZE	DWG.	NO.			REV	
	DRAWN	SJB	3/31/11	Α			BSTCA-P2C		A	
	RELEASED	LEASED DWO 3/31/11 WE				IGHT: 1.20 LB/FT			SHEET 1 OF 1	

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.