

MODEL V4D


(RENOVATION RIBBED ABRASIVE BARS)

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063-T5
- ② **ABRASIVE:** ALUMINUM OXIDE SILICON CARBIDE GRANDULES IN A UV PROTECTED, 2 PART, EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THAN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, GRAY, RED, BROWN, GREEN, BURGUNDY, BLUE AND BUFF, LUMINESCENT

- 7. **LENGTH:** 120" MAXIMUM
- 8. HOLES ARE DRILLED FOR A MIN. 3/16" x 1-1/4" CONCRETE FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

| LENGTH | QTY | COLOR |
|--------|-----|-------|
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |
| | | |

| | | | |
|---|------|---|--------------|
| PROJECT: | | | |
| ARCHITECT: | | | |
| CONTRACTOR: | | | |
| QTY: | | | |
| PART#: | | BSTRB-V4D | |
|  | | TITLE: N-RB40, Stair Tread, Bar Ribbed Abrasive, V-Nose, Drilled For Bolt In, | |
| 9300 73rd Avenue North Brooklyn Park, MN 55428 | | | |
| | NAME | DATE | SIZE |
| DRAWN | MDS | 12/14/11 | A |
| RELEASED | PE | 12/14/11 | |
| DWG. NO. | | REV | |
| Babcock STN BSTRB-V4D ShpDr | | A | |
| WEIGHT: VARIES | | | SHEET 1 OF 1 |

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.