



MODEL N3D-ECO

SPECIFICATIONS:

- 1. **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- 2. **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PART
EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF
STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
BLACK-BLUE, BLACK-GRAY
- 7. **LENGTH:** 12'0" MAXIMUM
- 8. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-
LUMINESCENT MATERIAL SHALL NOT BE LESS
THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		BSTSM-N3D-ECO			
 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:			
		Stair Tread, Single Stage, 3 Eco-tread Ribs, No Nose, Drilled for Bolt-In, 1" Photoluminescent Strip,			
NAME	DATE	SIZE	DWG. NO.	REV	
DRAWN	DKL	7/3/23	A	Babcock BSTSM-N3D-ECO ShpDr	A
RELEASED	GLN	7/3/23	WEIGHT: 1.27 LB		

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.