



MODEL N3E-T-ECO

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES ENCAPSULATED IN A WEAR AND WATER RESISTANT ELASTOMERIC NETWORK. 2 PART EPOXY, LOCKED INTO EXTRUDED CHANNELS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE

- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUE, BLACK-GRAY
- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

LENGTH	QTY	COLOR

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:		BSTSM-N3E-T-ECO			
 9300 73rd Avenue North Brooklyn Park, MN 55428		TITLE:			
		Stair Tread, Single Stage, 3 Eco-tread Ribs, No Nose, Aluminum Extruded Anchor 1" Photoluminescent Grit Strip			
	NAME	DATE	SIZE	DWG. NO.	REV
DRAWN	DKL	8/31/23	A	Babcock STN BSTSM-N3E-T-ECO ShpDr	A
RELEASED	GLN	8/31/23	WEIGHT: 1.27 LB		SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.