

MatDesign™ Aluminum Hinge Roll-up Mats

Models: BMD38P, BMD38R, BMD38V, BMD38G, BMD38X, BMD38E, BMD38U, BMD38B

LEED Category	Credit	Details	Possible Points	Product/Material Detail
Material and Resources (MR)	4	Recycled Content: Post-consumer + ½ Pre-consumer content	1 to 2 possible points	<ul style="list-style-type: none"> • Models BMD38P and BMD38R contain 37% pre-consumer and 19% post-consumer recycled content. • Model BMD38V contains 29% pre-consumer and 14.5% post-consumer recycled content. • Model BMD38E contains 50.7% pre-consumer, 21.7% post-consumer recycled content • Model BMD38U contains 35% pre-consumer and 17.7% post-consumer recycled content. • Model BMD38G contains 37% pre-consumer and 18% post-consumer recycled content. • Model BMD38B contains 31% pre-consumer and 16% post-consumer recycled content.
	5	Regional Material: Use building materials or products that have been extracted, harvested or recovered, as well as manufactured, within 500 miles of the project site	1 to 2 possible points	Not applicable. Extraction Point is not within 500 miles of manufacturing. Final Packaging Location: Brooklyn Park, MN 55428
	6	Rapidly Renewable Materials: Use rapidly renewable building materials and products for 2.5% of the total value of all building materials and products used in the project, based on cost. Rapidly renewable building materials and products are made from agricultural products that are typically harvested within a 10-year or shorter cycle.	1 possible point	Not applicable.
Indoor Environmental Quality (IEQ)	4.3	<p>Low-Emitting Materials—Flooring Systems</p> <p>All carpet installed in the building interior must meet the testing and product requirements of the Carpet and Rug Institute Green Label Plus1 program.</p> <p>All carpet adhesive must meet the requirements of IEQ Credit 4.1: Adhesives and Sealants, which includes a volatile organic compound (VOC) limit of 50 g/L.</p>	1 possible point	Not applicable. Product does not require adhesives or sealants in the field.
	5	Indoor Chemical and Pollutant Source Control:	1 possible	Meets the requirement if product is

	<p>Employ permanent entryway systems at least 10 feet long in the primary direction of travel to capture dirt and particulates entering the building at regularly used exterior entrances. Acceptable entryway systems include permanently installed grates, grills and slotted systems that allow for cleaning underneath. Roll-out mats are acceptable only when maintained on a weekly basis by a contracted service organization.</p>	points	installed at least ten (10) feet in the direction of traffic and properly maintained.
--	---	--------	---