

Exterior

ACCESS DOOR

The Babcock-Davis Exterior Access Door provides efficient access from the exterior of your building without compromising security or weather resistance.

FEATURES

COMPATIBLE WITH BUILDING KEY With the mortise lock prep option, you can match the mortise keying to that of your building's other access points.

TEMPERATURE CONTROL With 1.6 inch polyurethane insulation, the Babcock-Davis Exterior Door is constructed to protect your building from the harshest climates.

AIR + WATER PENETRATION TEST Independent lab testing for air leakage per ASTM E 283 and water leakage per ASTM E 331-00 assures the best protection against the elements.



DETAILS

DOOR 24 gauge Steel

FRAME 0.080 inch 6063-T5 Extruded Aluminum

SIZE

- Min: 12 inches by 12 inches
- Max: 48 inches by 60 inches

INSTALLATION Ceiling or Wall

FLANGE Exposed or Plaster/Stucco Bead

HINGE Stainless Steel Continuous Piano

FINISH

- Door: Paint Grip Finish
- Frame: Mill


INSULATION 1.7 inch Polyurethane; R-11

GASKETING EPDM Self-Adhesive, Continuous

FLANGES




1 inch Flange



Plaster/Stucco Bead

LATCHES



Non-Locking Handle



Screwdriver Cam Latch



Locking Handle



Mortise Lock Prep

ORDER GUIDE

| BASE | FLANGE | LATCH | WIDTH | X | LENGTH | OPTIONS |
|-----------|--|---|---|----------|--------|---|
| BX | | | | X | | |
| | T 1 inch Flange P Plaster/Stucco bead | A Non-Locking Handle C Screwdriver Cam Latch L Locking Handle M Mortise Lock (1-1/8") Prep | Standard Sizes (W x L) 12" x 12" 20" x 30" 24" x 36" 16" x 16" 24" x 24" 36" x 36" 18" x 18" 24" x 30" | | | A Aluminum Door C Drip Cap P Padlock Hasp S Type 304 Stainless Steel |

Rough opening is door size. Additional sizes available, call for more information.