

Halotron I

FIRE EXTINGUISHERS



The Halotron 1 fire extinguisher uses an EPA approved "Clean Agent" discharged as a rapidly evaporating liquid which leaves no residue. It effectively extinguishes Class A, B and C fires by cooling and smothering and it will not conduct electricity back to the user.

FINISH Glossy red polyester coated

MOUNTING Wall bracket

DISCHARGE Nozzle or hose & nozzle

BASE AGENT HydroChloroFluoro-Carbon

PRESSURE 125 P.S.I.

| MODEL | NOMINAL CAPACITY | UL RATING | HEIGHT | CYLINDER DIAMETER | RANGE OF STREAM | TYPE DISCHARGE |
|----------|------------------|-----------|---------|-------------------|-----------------|----------------|
| BEX-3101 | 1.4 Lbs. | 1B:C | 10" | 2-7/8" | 6' - 8' | Nozzle |
| BEX-3102 | 2.5 Lbs. | 2B:C | 15-1/2" | 3" | 6' - 10' | Nozzle |
| BEX-3105 | 5 Lbs. | 5B:C | 15-1/4" | 4-1/4" | 9' - 15' | Nozzle |

BC Dry Chemical

FIRE EXTINGUISHERS



The BC Multi-Purpose Dry Chemical fire extinguisher is used to provide protection against Class B and C fires.

FINISH Glossy red polyester coated

MOUNTING Wall bracket

DISCHARGE Nozzle or hose

AGENT BASE Sodium Bicarbonate

PRESSURE 195 P.S.I.

| MODEL | NOMINAL CAPACITY | UL RATING | HEIGHT | CYLINDER DIAMETER | RANGE OF STREAM | TYPE DISCHARGE |
|------------|------------------|-----------|---------|-------------------|-----------------|----------------|
| BEX-3302 | 2-1/2 Lbs. | 10B:C | 15-1/2" | 3" | 9' - 15' | Nozzle |
| BEX-3305 | 5 Lbs. | 10B:C | 15-1/4" | 4-1/4" | 12' - 18' | Hose |
| BEX-3305-3 | 5-1/2 Lbs. | 40B:C | 15-1/4" | 4-1/4" | 12' - 18' | Hose |
| BEX-3310 | 10 Lbs. | 60B:C | 20" | 5" | 15' - 21' | Hose |
| BEX-3320 | 20 Lbs. | 120B:C | 23-1/4" | 7" | 15' - 21' | Hose |

MOUNTING BRACKET

| MODEL | FITS SIZE |
|----------|---------------|
| BEX-3901 | 5 Lbs. |
| BEX-3902 | 6 Lbs. |
| BEX-3903 | 10 Lbs. |
| BEX-3909 | 5, 6, 10 Lbs. |
| BEX-3910 | 20 Lbs. |

Carbon Dioxide

FIRE EXTINGUISHERS



The Carbon Dioxide fire extinguisher is used to provide protection against Class B and C fires. Will not contaminate or leave residue on materials which it extinguishes.

FINISH Glossy red polyester coated

MOUNTING Wall bracket

DISCHARGE Horn or hose & horn

PRESSURE 735 P.S.I.

| MODEL | NOMINAL CAPACITY | UL RATING | HEIGHT | CYLINDER DIAMETER | OVERALL WIDTH | RANGE OF STREAM | TYPE DISCHARGE |
|----------|------------------|-----------|---------|-------------------|---------------|-----------------|----------------|
| BEX-3405 | 5 Lbs. | 5B:C | 17-3/4" | 5-1/4" | 8-1/4" | 3' - 8' | Horn |
| BEX-3410 | 10 Lbs. | 10B:C | 24" | 7" | 12" | 3' - 8' | Hose & Horn |
| BEX-3415 | 15 Lbs. | 10B:C | 30" | 7" | 12" | 3' - 8' | Hose & Horn |
| BEX-3420 | 20 Lbs. | 10B:C | 30" | 8" | 13" | 3' - 8' | Hose & Horn |

MOUNTING BRACKET

| MODEL | FITS SIZE |
|----------|-------------|
| BEX-3903 | 5 Lbs. |
| BEX-3904 | 10, 15 Lbs. |
| BEX-3905 | 20 Lbs. |
| BEX-3909 | 5 Lbs. |