

# Medium Security

## ACCESS DOOR

The Medium Security Access Door is manufactured with heavy-duty materials to prevent unwanted access to critical building components.



### DETAILS

**DOOR** 12 gauge Steel

**FRAME** 12 gauge Steel

#### SIZE

- Min: 8 inches by 8 inches
- Max: 36 inches by 48 inches

**INSTALLATION** Wall or Ceiling

**FLANGE** 1" Exposed, Drywall Bead or Plaster Bead

**HINGE** Concealed Continuous Piano

**FINISH** White Powder Primer Coat

### ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BM</b>				<b>X</b>		
	<b>T</b> 1 inch flange <b>W</b> Drywall bead <b>P</b> Plaster Bead	<b>D</b> Detention Lock Prep <b>K</b> Kurled Knob/Key Operated Latch Bolt <b>M</b> Mortise Lock (1-1/8") Prep <b>P</b> Pinned Hex Cam	<b>Standard Sizes (W x L)</b> 8" x 8"    18" x 18"    24" x 30" 10" x 10"    18" x 24"    24" x 36" 12" x 12"    20" x 30"    24" x 48" 12" x 18"    22" x 22"    30" x 30" 12" x 24"    22" x 30"    32" x 32" 14" x 14"    22" x 36"    36" x 36" 16" x 16"    24" x 24"    36" x 48"			<b>B</b> Galvannealed <b>M</b> Masonry Anchors <b>S</b> Type 304 Stainless Steel

*Rough opening is door size + 3/8 inch minimum. Additional sizes available, call for more information.*

# High Security

## ACCESS DOOR

The High Security Access Door provides secure access and is manufactured with detention-grade materials. This panel is engineered with heavy-duty butt hinges on the face of the door to prevent unwanted access.



### DETAILS

**DOOR** 10 gauge Steel

**FRAME** 3/16 inch Steel Angle - 2 inches by 2 inches

#### SIZE

- Min: 8 inches by 8 inches
- Max: 48 inches by 54 inches

**INSTALLATION** Wall or Ceiling

**FLANGE** 2" Exposed

**HINGE** Surface Mounted Heavy-Duty Butt

**FINISH** White Powder Primer Coat

### ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
<b>BHS</b>			<b>X</b>		
	<b>D</b> Detention Lock Prep <b>M</b> Mortise Lock (1-1/8") Prep <b>S</b> Security Screws	<b>Standard Sizes (W x L)</b> 12" x 12"    22" x 30"    24" x 40" 16" x 16"    24" x 24"    24" x 48" 18" x 18"    24" x 36"			<b>S</b> Type 304 Stainless Steel <b>Z</b> Continuous Concealed Hinge

*Rough opening is door size + 3/4 inch minimum. Additional sizes available, call for more information. \*Recommended for wall surfaces only. All doors come standard with Security Screws.*