babcockdavis®

Insulated Fire-Rated

ACCESS DOOR

Designed for wall and ceiling applications, this fire-rated Insulated Access Door is UL and Warnock-Hersey listed. Engineered with mineral fiber to assist in reducing heat transfer in the event of a fire.

FEATURES

FIRE-RATED Independently tested and labeled for 1½ hours for wall applications and 3 hours for ceiling applications.

EASY OPERATION This self-closing, self-latching door features an interior release for easy operation.

CUSTOM SIZING Custom sizes available from 6 inches by 6 inches to 48 inches by 48 inches.

DETAILS

DOOR 20 gauge Steel, Self-Closing, Self-Latching

FRAME 16 gauge Steel

SIZE
- Min: 6 inches by 6 inches
- BIT Max: 24 inches by 72 inches or 48 inches by 48 inches
- BIW/BIP Max: 36 inches by 48 inches

INSTALLATION Ceiling or Wall

HINGE
- BIT: Flush Continuous Piano
- BIW/BIP: Concealed Pin

FINISH White Powder Primer Coat

INSULATION 2 inch Thick, Fire-Rated Mineral Fiber, R-8

CERTIFICATION
- UL listed "B" label for 1½ hours (Wall)
- Warnock-Hersey listed for 3 hours (Ceiling)

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
BI				**X**		
	T 1 inch Flange **W** Drywall Bead **P** Plaster Bead	**K** Knurled Knob / Key Operated Latch Bolt **M** Mortise Lock (1⅛") Prep	**Standard Sizes** (W x L) 8" x 8" 10" x 10" 12" x 12" 12" x 18" 12" x 24" 14" x 14" 16" x 16" 18" x 18" 18" x 24" 20" x 30" 22" x 22" 22" x 30" 22" x 36" 24" x 24" 24" x 30" 24" x 36" 24" x 48"* 30" x 30"* 32" x 32"* 36" x 36"* 36" x 48"* 48" x 48"*			**B** Galvannealed **G** Gasketing **M** Masonry Anchors **S** Type 304 Stainless Steel

Rough opening is door size + ¼ inch minimum. Additional sizes available, call for more information.
**Wall application only.*

MATERIALS

White Powder Coat

FLANGES

1 inch Flange

Drywall Bead



Plaster Bead

LATCHES

Knurled Knob

Mortise Lock Prep