

Lume-A-Lite™

EXIT SIGNS

Lume-A-Lite Exit Signs provide a non-electric luminous egress routing system that is easily followed in the case of power loss in an emergency situation. Choose between one-sided or two-sided surface mount options. The material has been tested to UL 924 standards and meets current IBC, IFC, and NFPA code requirements.

FEATURES

BRIGHTNESS The glow-in-the-dark photoluminescent signs provides directions to the exit route. These exit signs are rated for 100 foot visibility with 90 minute emergency illumination.

DURABILITY The Exit Signs are long-lasting. It is designed with materials that last.

INSTALLATION EASE The Exit Signs come with mounting bracket hardware that can be installed with minimal tools. Installation and maintenance manuals are available at www.babcockdavis.com.



One-Sided Exit Sign



Two-Sided Exit Sign

DETAILS

MATERIAL Resin

COLOR Photoluminescent and red, green or black

MOUNTING Mechanically Fastened

SIZE 16 inches by 8 inches

CODE COMPLIANCE 2015/2018 IBC Section 1023 and 1025, 2015/2018 IFC Section 1023 and 1025

TEST STANDARD UL 924

MODELS

MODEL	COLOR	DESCRIPTION
BEM-SLE100R1-15.5X8.75	Red	
BEM-SLE100G1-15.5X8.75	Green	1-Sided
BEM-SLE100B1-15.5X8.75	Black	
BEM-SLE100R2-15.5X8.75	Red	
BEM-SLE100G2-15.5X8.75	Green	2-Sided
BEM-SLE100B2-15.5X8.75	Black	

COLORS



Red



Green



Black

