

# Lume-A-Lite™

## EXIT SIGNS

Lume-A-Lite Exit Signs provide a non-electric luminous egress routing system that is easily followed in the case of power loss in an emergency situation. Choose between one-sided or two-sided surface mount options. The material has been tested to UL 924 standards and meets current IBC, IFC, and NFPA code requirements.

### FEATURES

**BRIGHTNESS** The glow-in-the-dark photoluminescent signs provides directions to the exit route. These exit signs are rated for 100 foot visibility with 90 minute emergency illumination.

**DURABILITY** The Exit Signs are long-lasting. It is designed with materials that last.

**INSTALLATION EASE** The Exit Signs come with mounting bracket hardware that can be installed with minimal tools. Installation and maintenance manuals are available at [www.babcockdavis.com](http://www.babcockdavis.com).



One-Sided Exit Sign



Two-Sided Exit Sign

### DETAILS

**MATERIAL** Resin

**COLOR** Photoluminescent and red, green or black

**MOUNTING** Mechanically Fastened

**SIZE** 16 inches by 8 inches

**CODE COMPLIANCE** 2015/2018 IBC Section 1023 and 1025, 2015/2018 IFC Section 1023 and 1025

**TEST STANDARD** UL 924

### MODELS

MODEL	COLOR	DESCRIPTION
BEM-SE100R1-15.5X8.75	Red	
BEM-SE100G1-15.5X8.75	Green	1-Sided
BEM-SE100B1-15.5X8.75	Black	
BEM-SE100R2-15.5X8.75	Red	
BEM-SE100G2-15.5X8.75	Green	2-Sided
BEM-SE100B2-15.5X8.75	Black	

### COLORS



Red



Green



Black

