



1" PHOTOLUMINESCENT INSERT

MODEL STSM-P3D-ECO

SPECIFICATIONS:

- ① **BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-6
- ② **ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PART
EPOXY, LOCKED INTO EXTRUDED CHANNELS



PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

PROJECT:					
ARCHITECT:					
CONTRACTOR:					
QTY:					
PART#:					
babcockdavis		TITLE: Stair Tread, Single Stage, 3 0& V/^\^& Rib&, Photoluminescent Insert, Short Tip Nose, Alum Extruded Drilled, 1" Photoluminescent Insert			
9300 73rd Avenue North Brooklyn Park, MN 55428					
NAME	DATE	SIZE	DWG. NO.	REV	
DRAWN	DKL	3/6/19	A	Babcock BSTSM-P3E&OU&ShpDr	A
RELEASED	TR	3/6/19	WEIGHT:	SHEET 1 OF 1	