

PHOTOLUMINESCENT TAPE

MODEL P3.375E-ECO

(TWO STAGE RIBBED ECO-TREAD BARS)


SPECIFICATIONS:

- BASE:** EXTRUDED ALUMINUM ALLOY 6063 T-5
- ECOTREAD:** RECYCLED RUBBER SHEET
8MM RECYCLED RUBBER GRANULES
ENCAPSULATED IN A WEAR AND WATER
RESISTANT ELASTOMERIC NETWORK. 2 PARTS
- 3. **BASE FINISH:** MILL
- 4. **POURED CONCRETE STAIRS:** NOSING SHALL
TERMINATE NO MORE THEN 3" FROM END OF
STEPS
- 5. **CONCRETE FILLED STEEL PAN STAIRS:** NOSING
SHALL BE FULL LENGTH OF STEPS, LESS 1/8"
CLEARANCE
- 6. **COLOR:** BLACK (STANDARD), SAFETY YELLOW,
BLACK-BLUE, BLACK-GRAY

- 7. **LENGTH:** 12'0" MAXIMUM
- 8. **UL 1994 LISTED:** COMBINED WIDTH OF PHOTO-
LUMINESCENT MATERIAL SHALL NOT BE LESS
THAN 1"

LENGTH	QTY	COLOR

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF NYSTROM. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF NYSTROM IS PROHIBITED.

PROJECT:		
ARCHITECT:		
CONTRACTOR:		
QTY:		
PART#:	BSTTM-P3.375E-ECO	
	TITLE: Two Stage Rib, Stair Tread, Bar Ribbed Ecotread, Short Nose, Alum Extruded Anchor, Photoluminescent Tape	
9300 73rd Avenue North Minneapolis, MN 55428		
NAME DATE	SIZE DWG. NO.	REV
DRAWN DKL 4/3/23	A Babcock STN BSTTM-P3.375E-ECO ShpDr	A
RELEASED GLN 4/3/23	WEIGHT:	SHEET 1 OF 1