

(SINGLE STAGE ECO-TREAD RIBS)

## SPECIFICATIONS:

- $\langle 1 \rangle$  **Base**: Extruded Aluminum Alloy 6063 T-5
- (2) ECOTREAD: RECYCLED RUBBER SHEET

  8MM RECYCLED RUBBER GRANULES
  ENCAPSULATED IN A WEAR AND WATER
  RESISTANT ELASTOMERIC NETWORK. 2 PART
- 3. BASE FINISH: MILL
- 4. POURED CONCRETE STAIRS: NOSING SHALL TERMINATE NO MORE THEN 3" FROM END OF STEDS
- 5. CONCRETE FILLED STEEL PAN STAIRS: NOSING SHALL BE FULL LENGTH OF STEPS, LESS 1/8" CLEARANCE
- 6. COLOR: BLACK (STANDARD), SAFETY YELLOW, BLACK-BLUEL, BLACK-GRAY

- 7. **LENGTH**: 12'0" MAXIMUM
- COUNTER SUNK HOLES PRE-DRILLED FOR A #10 FASTENER SPACED 3" FROM ENDS AND APPROXIMATELY 12" TO 15" O.C.
- 9. UL 1994 LISTED: COMBINED WIDTH OF PHOTO-LUMINESCENT MATERIAL SHALL NOT BE LESS THAN 1"

QTY	COLOR
	QTY

PROJECT: ARCHITECT: CONTRACTOR: QTY: PART#: BSTSB-N1.375D-ECO TITLE: V120, Stair Tread, **babcock**davis Recycled Rubber, 2 Eco-Tread Ribs No Nose, Drilled For Bolt In, 9300 73rd Avenue North Brooklyn Park, MN 55428 NAME DATE SIZE DWG. NO. REV Babcock STN BSTSB-N1.375D-ECO ShpDr Α DRAWN 3/31/23 RELEASED GLN WEIGHT: .65 LB SHEET 1 OF 1 3/31/23

PROPRIETARY AND CONFIDENTIAL: THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF BABCOCK-DAVIS. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF BABCOCK-DAVIS IS PROHIBITED.

1