

Installation, Operation + Maintenance Manual

QuietFLEX

SURFACE MOUNT VINYL FRAMES

Model: BFQ38SV



QuietFLEX roll-up mat is constructed of LDPE hinges to reduce traffic noise. The lightweight aluminum rails make this mat easy to roll back for routine maintenance.

Introduction + Safety

Please read the complete instructions carefully before beginning any work. To ensure proper installation and performance of the product, the following actions must be completed by the installing contractor. Failure to do so will affect product warranty.

GENERAL SAFETY PRECAUTIONS Improper selection, installation, or use can cause personal injury or property damage. It is solely the responsibility of the user, through its own analysis to select products suitable for their specific application requirements, ensure they are properly maintained, and limit their use to its intended purpose. Follow proper local, state and federal regulations for proper installation and operation requirements.

Transportation + Storage

- Inspect all shipments and materials for missing or damaged components and hardware.
- o Material must be stored in a clean, dry location.

Preparation

- Locate the packing slip(s) and/or shop drawings.
- Verify that all products listed on the packing slip are included in the package.
- Check the products for damage. If products are damaged, report a freight claim immediately and leave the products in their packaging. If you sign for products without reporting damage you waive your right to a freight claim and will be responsible for their replacement cost.
- Read the instructions thoroughly before beginning installation.

Tool List

• Clean-up tools – see Maintenance

INSTALLATION

INSTALL THE MAT

- 1. Unroll the mat in desired location.
- 2. Save the installation and maintenance instructions and include them with the information that will be passed on to the owner or maintenance personnel.

MAINTENANCE

Continued maintenance is critical to the long-term safety and performance of the mat. Remove the mat and clean the recess periodically to prevent the surface from becoming uneven. Debris build up within the recess could lead to deflection in the mat and may possibly cause tripping hazards.

The type and schedule of maintenance of your mat will depend upon location and amount of traffic. See the outline below for cleaning instructions for the variety of tread insert materials.

Brush

- Clean the brush treads with a vacuum or broom.
- Do not use petroleum-based products to clean brush bristles. These types of solvents will damage or fade the treads.

EcoTread™

- Use a mild detergent and water with a soft bristle brush or microfiber mop.
- Do not use petroleum-based products to clean recycled rubber. These types of solvents will damage or fade the treads.

Premium Carpet

A good heavy-duty vacuum cleaner with a rotating brush is the most effective way to
routinely clean the carpet in your entrance mat. By vibrating the fibers, this type of
vacuum not only cleans the surface of the carpet, but also removes soil that is
imbedded into the pile. The rotating brush aids in keeping the pile upright for longer
lasting beauty.

- The heaviest traffic areas should be vacuumed daily and the light traffic areas as infrequently as weekly.
- Carpet should be deep cleaned with a hot water extraction cleaner once per month or when vacuuming will no longer remove the soil. This may be monthly, quarterly, or longer, depending upon soil and traffic conditions.
- Inspect the mat regularly for spots and stains, to reduce the possibility of them becoming permanent.
- Removing Spots
 - If the spot is semi-solid, scrape with a spoon or spatula and then blot with a damp sponge. Work from the edge of the spot to the center. This will keep the stain from spreading. If this procedure does not work, use a spot remover.
 - We recommend a dry system because it reduces solid build-up, won't leave floors wet and slippery, and there is no risk in damaging the carpet from dye bleeding. For most spills such as coffee, tea, pet stains, etc., a dry soil extractor works best.
 - Wet cleaning methods, including aerosols, foams, hot water extraction, or shampoo will work, but sometimes they leave sticky detergent residue that will accelerate soil build-up.
 - o For oily stains such as tar, grease, paint, etc., a non-flammable dry cleaning solvent works best. Be extremely careful when using dry cleaning solvent. Take care to check for color fastness before cleaning the entire surface. Put a few drops of stain remover in an inconspicuous area and press the area with a clean cloth for ten seconds. If the color fades or changes, discontinue use.

Ribbed Rubber

- Use a mild detergent and water to damp mop the rubber treads. To remove caked on mud, use a stiff brush.
- Do not use petroleum-based products to clean rubber. These types of solvents will damage or fade the treads.

Rugged Scrub®

• The most effective way to clean the treads is with a garden hose or high-pressure washer, as necessary. The treads can withstand pressure of up to 1,000 pounds per

- square inch. A good heavy-duty vacuum cleaner with a rotating brush will remove most dirt from your Rugged Scrub® treads during routine daily cleaning.
- Do not use petroleum-based products to clean Rugged Scrub®. These types of solvents will damage or dissolve the treads.

Serrated Aluminum Mats

• Clean the treads with a vacuum or broom first, and then mop the treads with standard floor cleaner.

Vinyl Abrasive Tread

- Clean the vinyl abrasive treads with a vacuum or broom.
- Do not use any hydrocarbon solvents such as kerosene, paint thinner or acetone to clean vinyl abrasive treads. These types of solvents will damage or fade the treads.

Vinyl Tread

- Use a mild detergent and water to damp mop the vinyl treads. To remove caked on mud, use a stiff brush.
- Do not use petroleum-based products to clean vinyl. These types of solvents will damage or fade the treads.

QUESTIONS?

For more information on installation, repair or replacement, please visit babcockdavis.com