

VINYL WALL COVERING

Model(s): BWCV-P

GENERAL DESCRIPTION



Vinyl Wall Covering can be used in a wide variety of applications. This sturdy wall covering is available various thicknesses and 70 color options with a classic embossed pattern.

Introduction + Safety

Please read the complete instructions carefully before beginning any work. To ensure proper installation and performance of the product, the following actions must be completed by the installing contractor. Failure to do so will affect product warranty.

GENERAL SAFETY PRECAUTIONS Improper selection, installation, or use can cause personal injury or property damage. It is solely the responsibility of the user, through its own analysis to select products suitable for their specific application requirements, ensure they are properly maintained, and limit their use to its intended purpose. Follow proper local, state and federal regulations for proper installation and operation requirements.

Transportation + Storage

- Inspect all shipments and materials for missing or damaged components and hardware.
- Material must be stored in a clean, dry location.

INSTALLATION

PREPARATION OF GOODS

Examine goods to ensure that pattern, color, quantity, and quality are as ordered. Separate goods by shade lot number and organize in roll number sequence.

PREPARATION OF SURFACE

Surfaces to be covered must be clean, smooth, dry, and structurally sound. Loose paint or other wallcoverings must be removed. In order to ensure maximum smoothness of installation, nail heads, nicks, gouges, and other surface imperfections should be sanded smooth and sealed. On new walls, dry wall joints should be taped, bedded, and sanded smooth.

Mold and mildew require moisture in order to grow and therefore it is important to check the walls with a suitable moisture meter. Moisture content should not exceed 4%. Excessive moisture in the wall needs to

be corrected prior to the installation of the wallcovering. Remove any mold and mildew from existing wall and treat surfaces to inhibit future growth.

Koroseal wallcovering can be installed over almost any surface which has been properly prepared. Do not hang vinyl over ball point pen writing, wax crayon, ink marker, oil-based stains, or any foreign matter that may bleed through the vinyl. Painted surfaces should be checked for possibility of pigment bleed-through. It is suggested that a pencil be used to mark vinyl or wall as pencil marks do not bleed.

Glossy surfaces should either be sanded to dull the surface or an application of Roman Pro 990; Rx 35™ Heavy Duty Primer should be made.

If future strippability is desired, a primer must be used. Some drywall joint compounds contrast with the drywall paper surface, showing strong light and dark colored areas. Very lightly colored, light-weight wallcoverings may show through due to their limited amount of opacity. Should this situation occur, we recommend that you use a primer, then Roman PRO-732 Extra Strength™ Clay Wallcovering Adhesive. If after applying three (3) strips, there is some questions of appearance, stop and contact your Koroseal sales representative. Attach wallcovering sheet using provided hardware thru the pre-drilled mounting holes.

OPERATION

Wall Covering are designed for years of wall protection. Perform annual inspections to ensure proper fitment and performance.

MAINTENANCE

- Use mild detergent to clean soiled surfaces. Pen marks, paint and graffiti generally wash off easily with mild soap and water. Completely rinse the surface with clean water when complete.

Note: Powdered cleansers and bleach cleaners should be used with care as they may leave a residue embedded in the cover surface. Properly rinsing with clean water will remove any residual residue.

- Tough marks or stains may require a heavy-duty cleaner such as “Crown Anti-Vandal Spray” or “DWR-II”. These specialized spot cleaners should only be used on small areas and tested for color fastness prior to applying in a highly visible area. Rinse thoroughly with clean water to remove the residue from these cleaners.

QUESTIONS?

For more information on installation, repair or replacement, please visit
www.Babcockdavis.com or call (888) 412-3726