7	6	5	4	3	
		·		•	ITEM NO.
					10
					20
(5	510)				30
					500
					510
		(30)			515
		(30)			520
(515)				525
					575
		525			
\searrow					
	v v				

8

D

С

В

RAILS, POSTS: 6061 T6 ALUMINUM ALLOY 1 /14" I.D. SCH 40

GATE: 1 1/4" TUBULAR ALUMINUM SELF CLOSING WITH COIL SPRING, ZINC PLATED

COUNTERFLASH MOUNTING BRACKETS: 3/16" ZINC PLATED STEEL FASTENED TO STEEL BACKING PLATE

А BOLTS: HEX HEAD BOLTS 3/8"-16 x 3/4" GRADE 5 ZINC PLATED

RAILING FITTINGS AND PLUGS: MANUFACTURER'S STANDARD CAST WITH SET SCREW HOLD

7

FITS HATCH SIZES UP TO 48" X 48"

(575)

(20)

10

CERTIFICATIONS: MEETS OSHA 29 CFR 1910.28 AND 1910.29 REQUIREMENTS FOR FALL PROTECTION; SUPPORTS 200 LBS. FORCE.

520

500

FINISH: SAFETY YELLOW POWDER COAT

5

babcock						
		d Avenue Park, MN				
		NAME				
	DRAWN	SJB	-			
ROHIBITED.	RELEASED	DWO	•			
	3					

proprietary and confidential; the information contained in this drawing is the sole property of babcock-davis. Any reproduction in part or as a whole without the written permission of babcock-davis is prohibited.
--

8

6

4

